# K Body REVO parallel clamp range















# Precise and gentle

Workpieces with sensitive surfaces can be clamped and spread exactly parallel to each other – even behind and on the side of the rail. Corners and recessed edges as well as pointed and round surfaces can also be perfectly aligned:

- due to extremely large clamping surfaces that are attached perpendicular to the rail
- due to three removable pressure caps that are repellent to glue, and also resistant to paint and grease solvents
- due to workpiece supports that prevent the workpiece from coming into contact with the rail





#### Versatile and well thought out

The clamps provide an enormous number of possible applications:

- due to ingenious accessories, such as tilting adapter, frame press set, clamp extension and table clamp
- the ergonomically formed 2-component symmetrical plastic handle with hexagon socket means the clamping force can be comfortably applied (max. torque 17 Nm)
- the continuously adjustable head for the KREV Vario version enables the clamp to be positioned in the middle of the workpiece for optimum weight distribution



## Powerful and safe

They securely clamp with a clamping force of up to 8,000 N:

- due to the metal-reinforced plastic housing
- due to the optimised sliding arm with double slide protection: It holds the clamp reliably with the set clamping force and prevents any unintentional slipping of the sliding arm in the unclamped condition





Order number	Opening	Throat depth	Spreading width e	Rail	Weight	PU	
	mm	mm	mm	mm	kg	qty.	V3
KRE30-2K	300	95	255-390	29 x 9	2.15	2	
KRE60-2K	600	95	255-730	29 x 9	2.76	2	
KRE80-2K	800	95	255-930	29 x 9	3.10	2	
KRE100-2K	1000	95	255-1130	29 x 9	3.45	2	
KRE125-2K	1250	95	255-1355	29 x 9	3.87	2	
KRE150-2K	1500	95	255-1610	29 x 9	4.28	2	
KRE200-2K	2000	95	255-2080	29 x 9	5.09	2	
KRE250-2K	2500	95	255-2580	29 x 9	6.05	2	
KREV100-2K	1000	95	260-1130	29 x 9	3.77	2	
KREV150-2K	1500	95	260-1610	29 x 9	4.25	2	
KREV200-2K	2000	95	260-2080	29 x 9	5.30	2	
KREV250-2K	2500	95	260-2580	29 x 9	6.30	2	
ı ۱		India			e		

K Body REVO parallel clamp KRE and

Vario K Body REVO parallel clamp KREV

# K

- Clamping force up to 8,000 N
- Very large parallel clamping surfaces with 3 removable pressure caps
- Metal-reinforced plastic housing and optimised sliding arm with double slide protection for more power and safety: The set clamping force is maintained and the sliding arm cannot unintentionally slip in the unclamped condition
- Can be converted without tools for spreading tasks
- High-quality 2-component symmetrical plastic handle with hexagon socket for the comfortable application of the clamping force (max. torque 17 Nm)
- KREV with continuously adjustable and fixable upper section for optimum positioning on the workpiece



>

>

5

>

YouTube

YouTube

# Accessories

Order number	Suitable for	Weight	PU	
number		kg	qty.	V
Variable jav	v KRE-VO			
KRE-VO	KRE / KREV / KR / KRV	0.59	12	
Tilting K Bo (Contents: 2	<b>dy clamp adapter KR-AS</b> 2 pcs./bag)			
KR-AS	KRE / KREV / KR / KRV	0.18	12	
Framing set (Contents: 4	t <b>KP</b> rail couplings and 4 adapters)			
KP	KRE / KREV / KR / KRV	0.55	12	
K Body para	allel clamp extender KBX			
KBX20	KRE / KREV / KR / KRV	0.75	12	
Table clam	o TK6			
TK6	KRE / KREV / KR / KRV	0.10	50	

😯 🖸 in

**O** 

#### KRE-VO:

 Steplessly adjustable and fixable upper section KRE-VO suitable for all BESSEY K body REVO KRE / KREV and KR / KRV
YouTube

#### KR-AS:

- Adapter with tilting clamping jaws with a tilt range of -15° to +15°
- Clamping on sloping and parallel surfaces

#### KP:

- KP Framing System (from 30 cm to 250 cm/12"-98") with four 90° KP Blocks
- Separately adjustable clamping force with 2 inserted
- clamps per cornerLightweight / easy
- to assemble

# **KBX20**:

 Connect any two K Body parallel clamps to increase the clamping capacity. The connector is made of robust aluminum
YouTube

## TK6:

- Especially for DIY applications and domestic appliances
- Special accessory for angle clamps WS 3/WS 6, screw clamp S 10 and K Body REVO parallel clamps KRE/KREV and KR/KRV to hold them to a work surface edge

BESSEY Tool GmbH & Co. KG = Mühlwiesenstraße 40 74321 Bietigheim-Bissingen, Germany Fon +49 7142 401-0 = Fax +49 7142 401-452 E-Mail: tool-info@bessey.de

More information www.bessey.de



Your dealer: